

# 1.8M C-band Rx/Tx Class III Antenna System



## PRODUCT SPECIFICATIONS

Detail Photos  
(on right from top to bottom)

Heavy-duty Az/EI Mount

Fine Azimuth and Elevation  
Adjustments

RF tested C-band Linear  
Polarized feed assembly



This reflector is  
thermoset-molded for  
strength and surface  
accuracy

## 1.8m C-band Linear Rx/Tx Class III Antenna System TYPE 183

The Skyware Global Type 183 1.8 m Class III Rx/Tx Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthen the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector and feed support arm. Heavy-duty lockdown bolts secure the mount to any 114 mm (4.50") O.D. mast and prevent slippage in high winds.

Hot-dip galvanizing is standard on this model for maximum environmental protection. A marinised version of this antenna is also available making it suitable for on-shore and offshore marine environments.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece precision offset thermoset-molded reflector.
- Heavy-duty galvanized Az/EI mount. Marinised version includes 2 part epoxy paint finish.
- Fine Azimuth and elevation adjustments.
- HD Galvanised support arm and alignment struts. Marinised version has all galvanized steel components finished with 2 part epoxy paint.
- Factory pre-assembled mount.
- Plated hardware for maximum corrosion resistance. Optional marinised version uses marine grade AISI 316 stainless steel hardware throughout.
- Includes Ku-band linear cross-polarized RxTx feed assembly.
- Heavy-duty Class III mount for 11 kg (25 lb) RF electronics (LNB & BUC).



Satcom solutions for the long haul

REV 11/14-01  
Page 1 of 2

1315 Outlet Center Drive, Smithfield, NC 27577 T + 1 919 934 9711 F + 1 919 989 2274 Sales @ Skyware Global.com

All designs, specification and availabilities of products and services presented in this bulletin are subject to change without notice. ©2014 Skyware Global


• PRODUCT SPECIFICATIONS

RF Performance	C-band Linear
Effective Aperture	..... 1.8m (71 in)
Operating Frequency	
TX	.....5.850 -6.725 GHz
RX	..... 3.400 -4.200 GHz
Polarization	..... Linear, Orthogonal
Gain (±0.3 dB)	
TX	..... 39.3 dBi @ 6.1 GHz
RX	..... 35.4 dBi @ 3.9 GHz
3 dB Beamwidth	
TX	..... 2.0° @ 6.1 GHz
RX	.....3.0° @ 3.9 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)	
2.5° < θ < 20°	..... 29-25 log θ
20° < θ < 26.3°	..... -3.5
26.3° < θ < 48°	..... 32-25 log θ
48° < θ < 180°	.....-10
Antenna Cross-Polarization	.....30db On Axis
Antenna Noise Temperature	
10° EL	.....41°K
20° EL	.....36°K
30° EL	.....33°K
VSWR	
Tx	..... 1.3:1
Rx	..... 1.5:1
Isolation (Port to Port)	
Tx	..... 60db
Rx	.....60db
Feed Interface	
Tx	..... Type N or CPR-137
Rx	.....CPR-229

All specifications typical)

1.8 m C-band Linear Rx/Tx Class III Antenna

Mechanical Performance	
Reflector Material	.....Glass Fiber Reinforced Polyester
Antenna Optics	..... One-Piece Offset Feed Prime Focus
Mount Type	..... Elevation over Azimuth
Elevation Adjustment Range	..... 10° - 90° Continuous Fine Adjustment
Azimuth Adjustment Range	.....360° Continuous, ± 10° Fine Adjustment
Mast Pipe Interface	..... 114 mm (4.50in) Diameter
Environmental Performance	
Wind Loading	
Operational	..... 50 mph (80 km/h)
Survival	..... 125 mph (200 km/h)
Temperature	..... -50°C to +80°C
Humidity	.....0 to 100% (Condensing)
Atmosphere	.....Standard Hardware Meets 500 Hrs SST Requirements (ASTM B-117) .....Marinised Option has AISI 316 stainless steel hardware
Solar Radiation	.....360 BTU/h/ ft <sup>2</sup>
Shock and Vibration	..... As Encountered during Shipping and handling



REV 11/14-01  
Page 2 of 2



Satcom solutions for the long haul